# Dell Axim X30 Combo

### **Physical Attributes**

**Dimensions** 77.2 x 122.4 x 15 millimeters

(width x height x depth): 3 x 4.8 x 0.6 inches

**Bounding Volume:** 141.7 cubic centimeters

Mass: 139 grams (battery included)

#### **Software Environment**

Microsoft Windows Mobile 2003 Second Edition for Pocket PC **Embedded Operating System:** 

Premium Edition

**Operating System Kernel:** Windows CE 4.21.1088 Build 14049

### Microprocessor, Chipset

CPU Clock: 312 MHz

CPU: Intel XScale PXA270

Width of Machine Word: 32 bit

**CPU** Core: Intel XScale

Level 1 cache: 32KB data cache / 32 KB instruction cache

**Instruction Set:** ARMv5TE

### Memory, Storage capacity

RAM type: **SDRAM** 

64 MB RAM capacity:

**ROM type:** Flash EEPROM

64 MB, including 31MB user-accessible non-volatile storage **ROM** capacity:

# Graphical subsystem

**Display Type:** color transflexive TFT display

Display Color Depth: 16 bit/pixel (65536 scales)

**Display Diagonal:** 3.5 " (89 millimeters)

**Display Resolution:** 240 x 320 (76800 pixels)

Viewable Display Size: 2.1 " x 2.8 " (53.4 x 71.2 millimeters)

114.2 pixel/inch (0.2225 millimeter/pixel) Dot Pitch:

Intel 2700G3 Multimedia Accelerator **Graphical Controller:** 

Frame Buffer / VRAM: 384 KB

# **Audio Subsystem**

**Audio Channel(s):** stereo sound

**Digital/Analog Converter** 

(Playing):

16 bit resolution

Microphone(s):mono soundLoudspeaker(s):mono soundAudio Output:3.5mm plug

**Audio Controller:** Wolfson WM9705

# **Control Peripherals**

**Positioning Device:** Touchscreen

**Primary Keyboard:** Not supported

**Directional Pad:** Four-way (with action button)

Scroll Wheel: Pressable non-rotary scroll wheel

#### **Interfaces**

MMC, SD, SDIO

**Expansion Interfaces:** Supports memory cards with capacity of up to 2GB and may

complies with some (not SD 2.0/HC) memory cards with higher

capacity than 2GB

USB 1.1 client, Full-Speed (12Mbit/s)

Proprietary connector

**Bluetooth** (802.15): Bluetooth 1.1, Internal antenna

Wireless LAN/Wi-Fi (802.11): IEEE 802.11b, 11 Mbit/s

Internal antenna

**Infrared Gate:** IrDA 1.2, 115200bit/s (SIR/CIR)

Serial (UART): RS-232, 115200 bit/s Proprietary connector

# **Power Supply**

**Battery Technology:** Lithium-ion battery

Battery Build: removable
Estimated Battery Life: 3 hours
Battery Capacity: 850 mAh

Estimated Average Current: 95 mA